

A stiff, silica thickened, very heavy viscosity, synthetic hydrocarbon grease intended for mechanical components requiring a heavy amount of damping. Benefits include good water resistance.

Lubricant Properties		Typical value	Test Method
<b>Recommended Service Range (°C)</b>		-10 to 120	
<b>Thickener</b>		Silica	
<b>Base oil</b>	Type	Polyalphaolefin	
	Kinematic viscosity	40°C 100°C	16830 cSt 1376 cSt
	Viscosity Index		323
	Flash point	°C	>200
	Pouring point	°C	-17
			ASTM D-445
			ASTM D-2270
			ASTM D-92
			ASTM D-97
Typical Properties of the Grease		Typical value	Test Method
<b>Color, Appearance</b>		Tan to Light Brown, Smooth	
<b>Penetration (1/10 mm)</b>	Unworked		225
	Worked	60X	220
		10K	243
	NLGI Grade		3
<b>Density</b>		25°C	0.87 g/cm <sup>3</sup>
<b>Oil Separation</b>	24 hour(s)	100°C	0
<b>Evaporation</b>	24 hour(s)	100°C	0.2
			ASTM D-70
			FTM 791, Method 321.2
			NYE CTM

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1508)

**Distributed by Newgate Simms Limited**

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom  
+44(0)1244 660771      www.newgatesimms.com      info@newgatesimms.com