

A silica thickened, light viscosity, synthetic hydrocarbon grease intended for mechanical components requiring a light amount of damping. Benefits include good water resistance.

Lubricant Properties			Typical value	Test Method
Recommended Service Range (°C)			-50 to 120	
Thickener			Silica	
Base oil	Type		Polyalphaolefin	
	Kinematic viscosity	100°C	111 cSt	ASTM D-445
		40°C	903 cSt	
		-40°C	708400 cSt	
	Viscosity Index		223	ASTM D-2270
	Flash point	°C	250	ASTM D-92
	Pouring point	°C	-43	ASTM D-97
Typical Properties of the Grease			Typical value	Test Method
Color, Appearance			Tan to Light Brown, Smooth	
Penetration (1/10 mm)	Unworked		270	ASTM D-217
	Worked	60X	280	
		10k	319	
		100k	373	
	NLGI Grade		2	
Density		25°C	0.86 g/cm ³	NYE CTM
Oil Separation	24 hour(s)	100°C	3.1	ASTM D-6184
Evaporation	24 hour(s)	100°C	0.2 %	NYE CTM

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1601)

Distributed by Newgate Simms Limited

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom
+44(0)1244 660771 www.newgatesimms.com info@newgatesimms.com